

(12) **United States Patent**
Ehlers et al.

(10) **Patent No.:** **US 8,585,510 B1**
(45) **Date of Patent:** **Nov. 19, 2013**

(54) **GOLF CLUB HEAD WITH IMPROVED AERODYNAMIC CHARACTERISTICS**

(75) Inventors: **Steven M. Ehlers**, Poway, CA (US); **D. Clayton Evans**, San Marcos, CA (US); **Matthew T. Cackett**, San Diego, CA (US)

(73) Assignee: **Callaway Golf Company**, Carlsbad, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 291 days.

(21) Appl. No.: **13/219,488**

(22) Filed: **Aug. 26, 2011**

Related U.S. Application Data

(60) Provisional application No. 61/378,340, filed on Aug. 30, 2010, provisional application No. 61/378,343, filed on Aug. 30, 2010, provisional application No. 61/378,502, filed on Aug. 31, 2010, provisional application No. 61/378,635, filed on Aug. 31, 2010, provisional application No. 61/379,039, filed on Sep. 1, 2010, provisional application No. 61/379,449, filed on Sep. 2, 2010, provisional application No. 61/380,007, filed on Sep. 3, 2010.

(51) **Int. Cl.**
A63B 53/02 (2006.01)

(52) **U.S. Cl.**
USPC **473/305; 473/307; 473/314; 473/315; 473/317; 473/327; 473/345; 473/349**

(58) **Field of Classification Search**
USPC **473/305, 307, 314, 315, 317, 327, 329, 473/342, 345, 349**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,587,758 A	6/1926	Charavay	
D118,594 S	1/1940	Heddon	
3,595,577 A	7/1971	Hodge	
3,693,978 A *	9/1972	East	473/314
4,065,133 A	12/1977	Gordos	
4,930,783 A	6/1990	Antonious	
5,120,061 A	6/1992	Tsuchida et al.	
5,163,682 A	11/1992	Schmidt et al.	
5,203,565 A	4/1993	Murray et al.	
5,251,896 A	10/1993	Gerlach	
5,318,297 A	6/1994	Davis et al.	
5,318,300 A	6/1994	Schmidt et al.	
5,335,908 A	8/1994	Bamber	
5,474,296 A	12/1995	Schmidt et al.	
5,575,725 A	11/1996	Olsavsky	
5,630,766 A *	5/1997	Granelli	473/313
5,674,136 A	10/1997	Gorse et al.	
5,830,084 A	11/1998	Kosmatka	
D401,991 S	12/1998	Collins	

(Continued)


Primary Examiner — Benjamin Layno

(74) *Attorney, Agent, or Firm* — Rebecca Hanovice; Michael A. Catania; Sonia Lari

(57) **ABSTRACT**

A golf club head (40) with a face component (50), an aft body (70), and an aerodynamic hosel (50) is disclosed herein. The hosel (50) is connected to the club head (40) at a head connection point (55) and to a shaft at a shaft connection point (57), and a YZ plane (85) defined by a y-axis and an x-axis that intersects the center of gravity (80) also intersects the head connection portion (55) of the hosel (50). In one further embodiment, a plane (95) aligned with the hosel (50) is parallel to an XZ plane (90) defined by the horizontal x-axis and the vertical z-axis. In another further alternative embodiment, a plane (95) aligned with the hosel (50) intersects the XZ plane 90.

13 Claims, 12 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,873,793 A	2/1999	Swinford	7,163,463 B2 *	1/2007	Mills	473/244
5,921,870 A	7/1999	Chiasson	7,163,468 B2	1/2007	Gibbs et al.	
5,938,541 A	8/1999	Allen et al.	7,163,470 B2	1/2007	Galloway et al.	
5,961,397 A	10/1999	Lu et al.	7,166,038 B2	1/2007	Williams et al.	
5,971,868 A	10/1999	Kosmatka	7,169,060 B2	1/2007	Stevens et al.	
6,007,432 A	12/1999	Kosmatka	7,214,143 B2	5/2007	Deshmukh	
6,027,414 A	2/2000	Koebler	7,226,366 B2	6/2007	Galloway	
6,048,278 A	4/2000	Meyer et al.	7,252,600 B2	8/2007	Murphy et al.	
6,244,976 B1	6/2001	Murphy et al.	7,258,626 B2	8/2007	Gibbs et al.	
6,332,847 B2	12/2001	Murphy et al.	7,258,631 B2	8/2007	Galloway et al.	
6,338,683 B1	1/2002	Kosmatka	7,273,419 B2	9/2007	Evans et al.	
6,354,962 B1	3/2002	Galloway et al.	7,278,927 B2	10/2007	Gibbs et al.	
6,368,234 B1	4/2002	Galloway et al.	7,291,075 B2	11/2007	Williams et al.	
6,386,990 B1	5/2002	Reyes et al.	7,306,527 B2	12/2007	Williams et al.	
6,398,666 B1	6/2002	Evans et al.	7,311,613 B2	12/2007	Stevens et al.	
6,406,378 B1	6/2002	Murphy et al.	7,314,418 B2	1/2008	Galloway et al.	
6,413,169 B1	7/2002	Kosmatka et al.	7,320,646 B2	1/2008	Galloway	
6,428,426 B1	8/2002	Helmstetter et al.	7,387,577 B2	6/2008	Murphy et al.	
6,435,977 B1	8/2002	Helmstetter et al.	7,390,269 B2	6/2008	Williams et al.	
6,440,008 B2	8/2002	Murphy et al.	7,396,296 B2	7/2008	Evans	
6,471,604 B2	10/2002	Hocknell et al.	7,402,112 B2	7/2008	Galloway	
6,478,692 B2	11/2002	Kosmatka	7,407,448 B2	8/2008	Stevens et al.	
6,491,592 B2	12/2002	Cackett et al.	7,410,428 B1	8/2008	Dawson et al.	
6,508,978 B1	1/2003	Deshmukh	7,413,519 B1	8/2008	Dawson et al.	
6,527,650 B2	3/2003	Reyes et al.	7,413,520 B1	8/2008	Hocknell et al.	
6,561,922 B2	5/2003	Bamber	7,419,440 B2	9/2008	Williams et al.	
6,565,452 B2	5/2003	Helmstetter et al.	7,431,667 B2	10/2008	Vincent et al.	
6,575,845 B2	6/2003	Galloway et al.	7,438,647 B1	10/2008	Hocknell	
6,582,323 B2	6/2003	Soracco et al.	7,448,960 B2	11/2008	Gibbs et al.	
6,592,466 B2	7/2003	Helmstetter et al.	7,455,598 B2	11/2008	Williams et al.	
6,602,149 B1	8/2003	Jacobson	7,476,161 B2	1/2009	Williams et al.	
6,607,452 B2	8/2003	Helmstetter et al.	7,491,134 B2	2/2009	Murphy et al.	
6,612,398 B1	9/2003	Tokimatsu et al.	7,494,424 B2	2/2009	Williams et al.	
6,623,377 B2	9/2003	Evans et al.	7,497,787 B2	3/2009	Murphy et al.	
6,663,504 B2	12/2003	Hocknell et al.	7,549,935 B2	6/2009	Foster et al.	
6,669,578 B1	12/2003	Evans	7,578,751 B2	8/2009	Williams et al.	
6,739,982 B2	5/2004	Helmstetter et al.	7,588,501 B2	9/2009	Williams et al.	
6,758,763 B2	7/2004	Murphy et al.	7,591,737 B2	9/2009	Gibbs et al.	
6,860,824 B2	3/2005	Evans	7,717,807 B2	5/2010	Evans et al.	
6,994,637 B2	2/2006	Murphy et al.	7,749,096 B2	7/2010	Gibbs et al.	
6,997,821 B2	2/2006	Galloway et al.	7,749,097 B2	7/2010	Foster et al.	
7,014,570 B2	3/2006	Evans et al.	D629,475 S	12/2010	Rollinson	
7,025,692 B2	4/2006	Erickson et al.	D630,690 S	1/2011	Rollinson	
7,070,517 B2	7/2006	Cackett et al.	2005/0032584 A1	2/2005	Van Nimwegen	
7,101,289 B2 *	9/2006	Gibbs et al. 473/329	2009/0318245 A1	12/2009	Yim et al.	
7,112,148 B2	9/2006	Deshmukh	2010/0009771 A1	1/2010	Newcomer	
7,118,493 B2	10/2006	Galloway	2010/0016095 A1	1/2010	Burnett et al.	
7,121,957 B2	10/2006	Hocknell et al.	2010/0016096 A1	1/2010	Burnett et al.	
7,125,344 B2	10/2006	Hocknell et al.	2010/0016097 A1	1/2010	Albertsen et al.	
7,128,661 B2	10/2006	Soracco et al.	2010/0178997 A1	7/2010	Gibbs et al.	
7,137,907 B2	11/2006	Gibbs et al.	2010/0292020 A1	11/2010	Tavares et al.	
7,144,334 B2	12/2006	Ehlers et al.	2010/0311517 A1	12/2010	Tavares et al.	
			2011/0136584 A1 *	6/2011	Boyd et al. 473/327	

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 1F




FIG. 1G




FIG. 1H




FIG. 11




FIG. 1J




FIG. 2






FIG. 3



**GOLF CLUB HEAD WITH IMPROVED
AERODYNAMIC CHARACTERISTICS****CROSS REFERENCES TO RELATED
APPLICATIONS**

The present application claims priority to U.S. Provisional Patent Application No. 61/378,340, filed on Aug. 30, 2010, U.S. Provisional Patent Application No. 61/378,343, filed on Aug. 30, 2010, U.S. Provisional Patent Application No. 61/378,502, filed on Aug. 31, 2010, U.S. Provisional Patent Application No. 61/378,635, filed on Aug. 31, 2010, U.S. Provisional Patent Application No. 61/379,039, filed on Sep. 1, 2010, U.S. Provisional Patent Application No. 61/379,449, filed on Sep. 2, 2010, and U.S. Provisional Patent Application No. 61/380,007, filed on Sep. 3, 2010.

**STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH OR DEVELOPMENT**

Not Applicable

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates to a golf club head having a hosel configuration that improves the aerodynamic qualities of the golf club head. More specifically, the present invention relates to wood-type golf club heads. Even more specifically, the present invention relates to drivers.

2. Description of the Related Art

Technical innovation in the configuration, material, construction and performance of golf clubs has resulted in a variety of new products. The advent of metals as a structural material has largely replaced natural wood for wood-type golf club heads, and is but one example of this technical innovation resulting in a major change in the golf industry. Another important example is the use of composite or plastic materials to form components of golf club heads, including the face, crown, and/or sole.

The Rules of Golf, established and interpreted by the United States Golf Association ("USGA") and The Royal and Ancient Golf Club of Saint Andrews, set forth certain requirements for a golf club head. The requirements for a golf club head are found in Rule 4 and Appendix II. Complete descriptions of the Rules of Golf are available on the USGA web page at www.usga.org. According to the Rules, the shaft of a golf club must be attached to a wood club head at the club head heel either directly or through a single plain neck and/or socket. The length from the top of the neck and/or socket to the sole of the club must not exceed 5 inches (127 mm), measured along the axis of, and following any bend in, the neck and/or socket.

Although the prior art has disclosed many variations of golf club heads, the prior art has failed to provide a club head with a hosel configuration that does not interfere with or have a negative affect on airflow over the crown of the club head during a swing.

BRIEF SUMMARY OF THE INVENTION

The inventors have found that, by moving the connection point between the hosel and the club head further away from the face of the club head in comparison with prior art hosel configurations, the hosel has less opportunity to create undesired air flow interference with an airstream as it moves over and around the crown of the club head during a swing. In

order to have optimal head and face alignment with the ball during set up, address, and impact, however, it is desirable to design the club head so that a shaft axis remains close to the face and is biased towards the heel. The present invention provides a solution to this problem by including a hosel configuration that has an optimal shaft axis location and an optimal hosel connection point such that the air flow interference can be reduced without negatively affecting the alignment of the club head with a golf ball.

One aspect of the present invention is a golf club head comprising a face component, an aft body comprising a crown, a sole, a heel section, and a toe section, a hosel having a head connection portion, and a center of gravity located at coordinates defined by an x-axis extending from the face towards a rear portion of the club head, a y-axis extending from the heel section towards the toe section, and a z-axis extending from the sole to the crown, and wherein a YZ plane defined by the y-axis and the z-axis that intersects the center of gravity also intersects the head connection portion. The present invention may further include a hosel plane that is parallel to an XZ plane defined by the x-axis and the z-axis. Alternatively, the present invention may further include a hosel plane that intersects an XZ plane defined by the x-axis and the z-axis.

Another aspect of the present invention is a golf club head comprising a face, an aft body comprising a crown and a sole, and a hosel having a head connection portion and a hosel plane, wherein the hosel plane is parallel to an XZ plane defined by an x axis extending horizontally from the face towards a rear portion of the golf club head and a z axis extending vertically from the sole to the crown.

Yet another aspect of the present invention is a golf club head comprising a face, an aft body comprising a crown and a sole, and a hosel having a head connection portion and a hosel plane, wherein the hosel plane intersects an XZ plane defined by an x axis extending horizontally from the face towards a rear portion of the golf club head and a z axis extending vertically from the sole to the crown.

The hosels of the embodiments described above may further have a cross-sectional shape is selected from a group consisting of circular, elliptical, airfoil, symmetrical, and non-uniform. In a further aspect of the present invention, at least part of the hosel has an airfoil cross-sectional shape, which may have a length of 0.25 to 1.50 inches, and more preferably a length that is less than or equal to 1.00 inch.

The embodiments described above may also have a striking portion with variable thickness. The golf club head embodiments described above may also have an overall shape selected from a group consisting of square, rectangular, and triangular. The embodiments described above may have a face or face component comprising a first material, a crown and sole comprising a second material, and a hosel comprising a third material. The embodiments described above may have a hosel constructed from of a lightweight material selected from the group consisting of composite, aluminum, titanium, magnesium, and plastic. The embodiments described above may have a hosel that is permanently affixed to the golf club head. Alternatively, the embodiments described above may have a hosel that is semi-permanently affixed to the golf club head.

**BRIEF DESCRIPTION OF THE SEVERAL
VIEWS OF THE DRAWINGS**

FIGS. 1A-1J are side perspective views of golf club heads according to first through tenth embodiments of the present invention.

3

FIG. 2 is a front view of an eleventh embodiment of the present invention.

FIG. 3 is a side perspective view of the golf club head shown in FIG. 2.

FIG. 4A is a top view of the golf club shown in FIG. 1A.

FIG. 4B is a top view of a golf club head according to a twelfth embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is generally directed to a golf club head with a novel hosel configuration that creates reduced interference with airflow over the crown of the club head during a swing in comparison with hosel configurations of the prior art.

As shown in FIG. 1A, a preferred embodiment of the golf club head 40 is generally designated. The golf club head 40 may have a hollow interior (not shown). As shown in FIG. 1A, the club head 40 is generally composed of a face 60, an aft body 70 comprising a crown 62 and a sole 64, and a hosel 50. In this embodiment, the hosel is swept back and straight. The club head 40 also may optionally have a ribbon, skirt, or side portion (not shown) disposed between the crown 62 and sole 64 portions. The golf club head 40 is preferably partitioned into a heel section 66 nearest the shaft hosel 50, a toe section 68 opposite the heel section 66, and a rear section 75 opposite the face component 60. The hosel 50 is connected to the club head 40 at a head connection portion 55 and to a shaft (not shown) at a shaft connection portion 57.

The golf club head 40 shown in FIG. 1A also has a center of gravity 80 located on a Cartesian coordinate system. The x-axis of the coordinate system extends along a horizontal axis extending from the face 60 to the rear section 75, the y-axis extends along a horizontal axis extending from the heel section 66 to the toe section 68, and the z-axis extends along a vertical axis from the sole 64 to the crown 62. In a most preferred embodiment of the present invention, a YZ plane 85 defined by the y-axis and the x-axis that intersects the center of gravity 80 also intersects the head connection portion 55 of the hosel 50. As shown in FIGS. 1A-1J, the YZ plane 85 can intersect any part of the head connection portion 55, but most preferably intersects the midpoint of the head connection portion 55 as shown in FIG. 1A. This configuration creates aerodynamic benefits and can reduce overall head drag.

FIG. 1B shows a hosel 50 having a double bend curved design. FIG. 1C shows a hosel 50 having a single, concave bend design. FIG. 1D shows a hosel 50 having a single bend, straight design. FIG. 1E shows a hosel 50 having a double bend straight design. FIG. 1F shows a hosel 50 having a single, convex bend design. FIG. 1G shows a hosel 50 having a swept back, straight design and a side-mounted shaft connection 57, which extends towards the heel section 66 along the y-axis. FIG. 1H shows a hosel 50 having a swept back, straight design with a single bend and a side-mounted shaft connection 57, which extends towards the heel section 66 along the y-axis. FIG. 1I shows a hosel 50 having a double bend, swept back, straight design. FIG. 1J shows a hosel 50 having an alternative double bend, straight design. In each of FIGS. 1A-1J, the YZ plane 85 intersects both the center of gravity 80 and the head connection portion 55 of the hosel 50. The YZ plane 85 is also shown intersecting the center of gravity 80 and the head connection portion 55 of the hosel 50 in FIGS. 2 and 3.

In another embodiment of the present invention, shown in FIG. 4A, a plane 95 aligned with the hosel 50 is parallel to an XZ plane 90 defined by the horizontal x-axis and the vertical z-axis. This is further illustrated by the plane 95 shown FIG.

4

1A. In an alternative embodiment, shown in FIG. 4B, a plane 95 aligned with the hosel 50 intersects the XZ plane 90. These alternative embodiments may be combined with the embodiments disclosed above, as shown in FIGS. 1A, 4A, and 4B. These configurations can create aerodynamic benefits and reduce overall head drag.

In some embodiments of the present invention, the cross-sectional shape of the hosel of may be circular, elliptical, airfoil, symmetrical, or non-uniform to encourage aerodynamic airflow around, over, across, and by the hosel during a swing. Furthermore, the diameters or thicknesses of segments of the hosel of the present invention may, in some embodiments, vary and/or taper to help reduce the drag of air around, over, across, and by the hosel during a swing. Lengths of segments of the hosel also may vary. For example, in an embodiment wherein a segment of the hosel has an airfoil cross-section, that segment preferably has a length of 0.25 to 1.50 inch, and more preferably a length of no more than 1.00 inch.

The hosel of the present invention may be permanently and rigidly affixed to the golf club head, or may be semi-permanently and rigidly affixed, such that the hosel may be adjustably attached to the golf club head to customize the loft, lie, and face angles of the club head for a golfer wishing to alter these variables to his or her liking. In one embodiment, the hosel of the present invention is attached to the club head by affixing it to a spud shaft that is permanently and rigidly affixed to the club head for the express purpose of positioning, locating, and rigidly affixing the hosel in a desired orientation on the club head. In another embodiment, the hosel design of the present invention may be attached to the club head by affixing it into a receiving cavity or a receiving mating location that is designed into the club head for the express purpose of positioning, locating, and rigidly affixing the hosel in a desired orientation onto the club head.

The hosel of the present invention may also have portions that are semi-permanently affixed to one another to modify the way that the shaft and club head are oriented with respect to one another when the hosel is rigidly affixed to the club head. This configuration may be used to modify the loft, lie, and/or face angle parameters of the golf club head as desired by the golfer.

The golf club head of the present invention may be made from various materials, including, but not limited to, titanium and titanium alloys, magnesium, aluminum, tungsten, carbon or graphite composite, plastic, stainless steel, etc. In some embodiments, the entire club head is made of one material. In other embodiments, the club head is made of two or more materials. The golf club of the present invention may also have material compositions such as those disclosed in U.S. Pat. Nos. 6,244,976, 6,332,847, 6,386,990, 6,406,378, 6,440,008, 6,471,604, 6,491,592, 6,527,650, 6,565,452, 6,575,845, 6,478,692, 6,582,323, 6,508,978, 6,592,466, 6,602,149, 6,607,452, 6,612,398, 6,663,504, 6,669,578, 6,739,982, 6,758,763, 6,860,824, 6,994,637, 7,025,692, 7,070,517, 7,112,148, 7,118,493, 7,121,957, 7,125,344, 7,128,661, 7,163,470, 7,226,366, 7,252,600, 7,258,631, 7,314,418, 7,320,646, 7,387,577, 7,396,296, 7,402,112, 7,407,448, 7,413,520, 7,431,667, 7,438,647, 7,455,598, 7,476,161, 7,491,134, 7,497,787, 7,549,935, 7,578,751, 7,717,807, 7,749,096, and 7,749,097, the disclosure of each of which is hereby incorporated in its entirety herein.

The golf club head of the present invention may be constructed to take various shapes, including traditional, square, rectangular, or triangular. In some embodiments, the golf club head of the present invention takes shapes such as those disclosed in U.S. Pat. Nos. 7,163,468, 7,166,038, 7,169,060,

5

7,278,927, 7,291,075, 7,306,527, 7,311,613, 7,390,269, 7,407,448, 7,410,428, 7,413,520, 7,413,519, 7,419,440, 7,455,598, 7,476,161, 7,494,424, 7,578,751, 7,588,501, 7,591,737, and 7,749,096, the disclosure of each of which is hereby incorporated in its entirety herein.

The golf club head of the present invention may also have variable face thickness, such as the thickness patterns disclosed in U.S. Pat. Nos. 5,163,682, 5,318,300, 5,474,296, 5,830,084, 5,971,868, 6,007,432, 6,338,683, 6,354,962, 6,368,234, 6,398,666, 6,413,169, 6,428,426, 6,435,977, 6,623,377, 6,997,821, 7,014,570, 7,101,289, 7,137,907, 7,144,334, 7,258,626, 7,422,528, 7,448,960, 7,713,140, the disclosure of each of which is incorporated in its entirety herein. The golf club of the present invention may also have the variable face thickness patterns disclosed in U.S. Patent Application Publication No. 20100178997, the disclosure of which is incorporated in its entirety herein.

From the foregoing it is believed that those skilled in the pertinent art will recognize the meritorious advancement of this invention and will readily understand that while the present invention has been described in association with a preferred embodiment thereof, and other embodiments illustrated in the accompanying drawings, numerous changes, modifications and substitutions of equivalents may be made therein without departing from the spirit and scope of this invention which is intended to be unlimited by the foregoing except as may appear in the following appended claims. Therefore, the embodiments of the invention in which an exclusive property or privilege is claimed are defined in the following appended claims.

We claim as our invention:

- 1. A golf club head comprising
 - a face component;
 - an aft body comprising a crown, a sole, a heel section, and a toe section;
 - a hosel having a head connection portion; and
 - a center of gravity located at coordinates defined by an x-axis extending from the face towards a rear portion of the club head, a y-axis extending from the heel section towards the toe section, and a z-axis extending from the sole to the crown;

6

wherein a YZ plane defined by the y-axis and the z-axis that intersects the center of gravity also intersects the head connection portion, and

wherein the hosel comprises a hosel plane that intersects and XZ plane defined by the x-axis and the z-axis.

5

2. The golf club head of claim 1, further comprising a hosel plane that is parallel to an XZ plane defined by the x-axis and the z-axis.

3. The golf club head of claim 1, wherein a cross-sectional shape of the hosel is selected from a group consisting of circular, elliptical, airfoil symmetrical, and non-uniform.

10

4. The golf club head of claim 3, wherein at least part of the hosel has an airfoil cross-sectional shape.

15

5. The golf club head of claim 4, wherein the part of the hosel having an airfoil cross-sectional shape has a length of 0.25 to 1.50 inches.

20

6. The golf club head of claim 5, wherein the part of the hosel having an airfoil cross-sectional shape has a length that is less than or equal to 1.00 inch.

25

7. The golf club head of claim 1, wherein the face component has a striking portion with variable thickness.

30

8. The golf club head of claim 1, wherein an overall shape of the golf club head is selected from a group consisting of square, rectangular, and triangular.

35

9. The golf club head of claim 1, wherein the face component comprises a first material, the crown and sole comprise a second material, and the hosel comprises a third material.

40

10. The golf club head of claim 1, wherein the hosel is constructed from of a lightweight material selected from the group consisting of composite, aluminum, titanium, magnesium, and plastic.

45

11. The golf club head of claim 1, wherein the hosel is permanently affixed to the golf club head.

50

12. The golf club head of claim 1, wherein the hosel is semi-permanently affixed to the golf club head.

55

13. The golf club head of claim 1, wherein the YZ plane intersects a midpoint of the head connection portion.

* * * * *